

SAFETY DATA SHEET

HP1

Page 1

Issued: 28/04/00

Revision No: 1

Danum Laboratory Services

2 Duncroft Grove

Rossington

Doncaster DN11 0UL

Tel: 01302 864668

Fax: 01302 860880

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: HP1

Product code: RD3101

Use / description of product: Corrosive. Oily liquid.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient 1: DLS REAGENT HP 1 >90%

[C] R35;

3. HAZARDS IDENTIFICATION

Main hazards: Causes severe burns.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: If conscious, give 1 pint of water to drink immediately.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder. Foam Dry powder Mist Vapourising Liquids.
Alcohol foam Do not use water.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not allow large quantities to enter local drainage systems

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: Self-contained breathing apparatus must be used in handling.

Hand protection: Protective gloves.

[cont...]

HP1

Eye protection: Safety goggles. Face-shield.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Oily liquid.

Colour: Colourless

Odour: Odourless

Solubility in water: Miscible liberating much heat.

pH: 0-1

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Never add water to this product

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION**12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS**

Waste disposal: Dispose of as normal industrial waste.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 2796

ADR Class: 8

Hazard ID no: 80

Labelling: 8

Shipping name: BATTERY FLUID, ACID

IMDG / IMO

UN no: 2796

Class: 8

Packing group: II

EmS: 8-06

Marine pollutant: NO

Labelling: 8

IATA / ICAO

UN no: 2796

Class: 8

Packing group: II

Packing instructions: 813

[cont...]

Quantity 30 L

Labelling: 8

15. REGULATORY INFORMATION

Hazard symbols: Corrosive.



Risk phrases: R35: Causes severe burns.

Safety phrases: S2: Keep out of the reach of children.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S30: Never add water to this product.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R35: Causes severe burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.