SAFETY DATA SHEET

MP1A

Issued: 03/05/00

Revision No: 1

Danum Laboratory Services

2 Dunscroft Grove

Rossington

Doncaster DN11 0UL Tel: 01302 864668 Fax: 01302 860880

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: MP1A

Product code: RD3035

Use / description of product: Highly flammable. Liquid.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient 1: DLS REAGENT MP 1A >90%

[F] R11;

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: If conscious, give 1 pint of water to drink immediately.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Water. Do not use foam Dry powder Vapourising Liquids. Do not use carbon dioxide.

Exposure hazards: Highly flammable. Vapour/air mixture explosive. Decomposes to emit acrid smoke and

irritating fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not allow large quantities to enter local drainage systems

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

SAFETY DATA SHEET

MP1A

Eye protection: Safety goggles. Face-shield.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Slight

Solubility in water: Miscible in all proportions

Melting point/range°C: -89

Flash point°C: 12

pH: 1-2

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Air. Oxygen Store at temperature below 8 degrees.

Materials to avoid: Oxidising agents. Aluminium.

Haz. decomp. products: Peroxides on prolonged storage

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste disposal: Dispose of as normal industrial waste.

Disposal of packaging Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1274

ADR Class: 3
Hazard ID no: 33

Labelling: 3

Shipping name: N-PROPANOL (PROPYL ALCOHOL, NORMAL)

IMDG / IMO

UN no: 1274

Class: 3.2

Packing group: II

EmS: 3-06

Marine pollutant: NO

Labelling: 3

IATA / ICAO

UN no: 1274

Class: 3

SAFETY DATA SHEET

MP1A

Packing group: II

Packing instructions: 307

Quantity 60 L

Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.

炒

Risk phrases: R11: Highly flammable.

Safety phrases: S2: Keep out of the reach of children.

S7: Keep container tightly closed.

S16: Keep away from sources of ignition - No smoking.

Note: The regulatory information given above only indicates the principal regulations

specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or

provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R11: Highly flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any damage

resulting from handling or from contact with the above product.