

SAFETY DATA SHEET
VHR ACIDITY TITRANT

Page 1

Issued: 27/04/00

Revision No: 1

Danum Laboratory Services
2 Duncroft Grove
Rossington
Doncaster DN11 0UL
Tel: 01302 864668
Fax: 01302 860880

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: VHR ACIDITY TITRANT

Product code: TC2001VHR

Use / description of product: Corrosive. Liquid.

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient 1: DLS VHR ACIDITY TITRANT >90%
[C] R35;

3. HAZARDS IDENTIFICATION

Main hazards: Causes severe burns.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: If conscious, give 1 pint of water to drink immediately.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Water. Carbon dioxide. Dry chemical powder. Foam Vapourising Liquids.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not allow large quantities to enter local drainage systems

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hand protection: Protective gloves.

Eye protection: Safety goggles. Face-shield.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

[cont...]

SAFETY DATA SHEET
VHR ACIDITY TITRANT**9. PHYSICAL AND CHEMICAL PROPERTIES**

State: Liquid
Colour: Colourless
Odour: Odourless
Solubility in water: Miscible in all proportions
pH: 13-14

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat.
Materials to avoid: Chloroform/methanol mixtures Strong acids. Zirconium Zinc.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION**12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS**

Waste disposal: Dispose of as normal industrial waste.
Disposal of packaging Dispose of as normal industrial waste.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1824
ADR Class: 8
Hazard ID no: 80
Labelling: 8
Shipping name: SODIUM HYDROXIDE, SOLUTION

IMDG / IMO

UN no: 1824
Class: 8
Packing group: II
EmS: 8-06
Marine pollutant: NO
Labelling: 8

IATA / ICAO

UN no: 1824
Class: 8
Packing group: II
Packing instructions: 813
Quantity 30 L
Labelling: 8

SAFETY DATA SHEET
VHR ACIDITY TITRANT**15. REGULATORY INFORMATION**

Hazard symbols: Corrosive.



Risk phrases: R35: Causes severe burns.

Safety phrases: S2: Keep out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39: Wear suitable gloves and eye / face protection.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R35: Causes severe burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.